

Cat 5e Keystone Jacks

D-Link Category 5e keystone jacks are RJ45 8P 8C 50u jacks suitable for 22-26 AWG stranded and solid wire, compatible with both 110 & Krone punch down tools. They are available in universal labels color coded for T568A and T568B wiring schemes and fit in high density keystone patch panel. It supports IEC 60603-7-4 and complied with ANSI/TIA/EIA-568-C.2 standard.



SPECIFICATIONS

RJ45 Jack:	Housing: ABS+PC, UL 94V-0, with optional color
	Contact Bracket: PC, UL 94V-2, transparent color
RJ45 Jack Contact:	Material-phosphor bronze with nickel plated
	Finish: 50 micro-inch gold plated on plug contact area
IDC:	Housing- PC + glass fiber, UL 94V-2
	Terminal: phosphor bronze with tin plated
IDC CAP:	ABS, UL 94V-0
Insertion Cycles:	750 times
Insertion Force:	20N (Max)
Operating Temperature:	-10°C to 60°C
Storage Temperature:	-10°C to 80°C
Contact Resistance	
Variation:	20 Milliohms
Insulation Resistance:	> 100 Megaohms

ORDERING INFORMATION

CAT 5E Keystone Jacks		
Part Code	Description	Color Code
NKJ-5EWHI1B21	Cat5E UTP Keystone Jack	White
NKJ-5EBLU1B21	Cat5E UTP Keystone Jack	Blue
NKJ-5ERED1B21	Cat5E UTP Keystone Jack	Red
NKJ-5EGRN1B21	Cat5E UTP Keystone Jack	Green
NKJ-5EYEL1B21	Cat5E UTP Keystone Jack	Yellow



D-Link (India) Limited
Kalpataru Square, 2nd Floor, Kondivita Lane, Andheri-East, Mumbai-400059
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2010 D-Link Corporation. All rights reserved. Release 01 (May 2010)