

At D-Link, we adopt high precision equipments in fiber connectors product line providing the highest levels of reliability and performance. Each connector has a 2.5mm ceramic ferrule which is housed in a nickel plated brass housing. Available in both Single and Multi mode, connectors come with a 900µm and 3mm strain relief boot. Good for use with pigtail and buffered fiber cables.

FEATURES

- High Precision Ceramic Ferrule
- High Precision Nickel Plated Brass housing
- Come with a 900µm and 3mm strain relief boot



SPECIFICATIONS

| Measure | ST Connector |
|---|--|
| Insertion Loss dB (Single and Multi Mode) | < 0.3 |
| Return Loss | > 50dB UPC Style Ferrule |
| Pigtail Boot | 900µm black (MM) yellow (SM) |
| Cable Boot | 3mm black, 2mm upon request |
| Mating Cycle | Up to 1000 times |
| Ferrule Diameter | 2.5mm ± 0.001 |
| Ferrule Tolerance Single Mode | 126 ± 0.5µm internal |
| Ferrule Tolerance Multi Mode | 127 ± 0.5µm internal |
| Finish | Pre-radiused PC end, radius 10 to 25mm |
| Operating Temperature | - 40°C to + 85°C |
| Meet Standard | IEC61754-20 Optical Fiber Connector Interface |
| Durability | IEC61300-2-2 Fiber Optic Interconnecting Devices |
| Performance | IEC61753-1 Optical Fiber interconnecting devices and passive components performance standard |

ORDERING INFORMATION:

| | |
|-------------|-----------------------|
| NCO-FMSST09 | Connector MM ST Style |
| NCO-FSSST09 | Connector SM ST Style |

D-Link (India) Limited
Kalpataru Square, 2nd Floor, Kondivita Lane, Andheri-East, Mumbai-400059
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2010 D-Link Corporation. All rights reserved. Release 01 (May 2010)